HOW TO?



Set up a frame grabber

C-RED 2, C-RED 2 ER, C-RED 2 Lite & C-RED 3

v1. 11/06/2021



Table

GL	_OSS	ARY	. 1
1.	П	NTRODUCTION	. 2
2.	N	MATERIAL LIST	. 2
3.	F	PRECAUTIONS TO HANDLE THE FRAME GRABBER	. 3
	3.1.	Open the computer	. 3
		B.1.1. Inside view of the computer	
	3.2.	Remove the frame grabber	. 4
	3	3.2.1. Free PCIe slot location	. 5
	3.3.	Place the new frame grabber	. 5
	3.4.	Fix the new frame grabber	. 6
	3.5.	Connect the cables	. 6
	3.6.	Ready to go!	. 7

Glossary

- HDR: High Dynamic Range
- ADU: Analog Digital Unit
- **HG**: High Gain
- LG: Low Gain
- ADC: Analog to Digital Converter
- NUC: Non Uniformity Correction
- IWR: Integrate While Read
- ITR: Integrate Then Read
- FPS: Frames Per Second
- CDS: Correlated Double sample



1. Introduction

This document is a tutorial explaining how to set up a frame grabber. In this tutorial, we will use a C-RED 3 camera and a MATROX eV-CL grabber.

2. Material list

Frame grabber box

Camera pelicase



Pair of CameraLink® cables

3. Precautions to handle the frame grabber



Frame grabber

A


Please wear a anti-static shock bracelet. The card is a sensitive component.

3.1. Open the computer




Open up the computer by removing the lateral board. A few screws may need to be removed.

3.1.1. Inside view of the computer




3.2. Remove the frame grabber





Please wear an anti-static shock bracelet. The framegrabber should be stored in an anti-static paper and put back in its box.

3.2.1. Free PCIe slot location



Free PCIe slot

3.3. Place the new frame grabber



Anti-static shock bracelet


Free PCIe slot

Frame grabber



Please handle the frame grabber with care. Beware not to make any mechanical shock with the computer, as this may break the components on the card.

3.4. Fix the new frame grabber



CameraLink® cable pair

Connect the CameraLink® cables to the connectors on the frame grabber.

3.5. Connect the cables



Lock the screws and put the computer panel back in place.



3.6. Ready to go!



ABOUT FIRST LIGHT IMAGING: When astronomers and engineers design a new scientific instrument, there is a very special moment. It happens the first time the instrument is set on the telescope, looking at the sky. When light coming from the universe trickles down the system and ultimately falls on the detector. From this moment on, observations can begin, theories can be tested, science can be made.

We call this moment the First Light.

At First Light Imaging, we make the invisible visible. Since 2011, we design and manufacture cutting-edge scientific cameras that combine exceptional sensitivity and very high frame rates in both the visible and infrared (SWIR) spectra, based on state-of-the-art sensors (EMCCD, CMOS, e-APD, and InGaAs). Coming from French academic research laboratories, multiple award-winning, First Light Imaging focuses on providing customers in astronomy, research, biology, and high-end industry with the utmost performance capabilities.

www.first-light-imaging.com